

# **Safety Data Sheet**

Issue date 23-Feb-2015 Version 1

# 1. Identification of the Substance/Preparation and of the Company/Undertaking

**Product Identifier** 

Product name CHAMPION SPRAYON VISTA CLEER GLASS CLEANER

Chemical name 7-7694-1

Other means of identification

Product code FG 438-5155-7 Synonyms Glass Cleaner

Recommended use of the chemical and restrictions on use

Recommended Use Glass surfaces.

Uses advised against DO NOT USE ON FLOORS

Details of the supplier of the safety data sheet

Supplier Address Chase Products Co. 2727 Gardner Road Broadview, IL 60155 708-273-1121

**Emergency Telephone Number** 

Company Phone Number 708-865-1000 24 Hour Emergency Phone Number 1-800-255-3924

Emergency telephone ChemTel 1-800-255-3924

Manufacturer Address Chase Products Co. 2727 Gardner Road

Broadview, IL 60155 708-273-1121

# 2. Hazards Identification

## Classification

Acute toxicity - Inhalation (Gases)	Category 4
Gases Under Pressure	liquefied gas

# Label Elements

# **EMERGENCY OVERVIEW**

#### Warning

#### hazard statements

HARMFUL IF INHALED

Contains gas under pressure; may explode if heated



**Appearance** Clear liquid that will be aerosolized.

Physical State Foam Aerosol

Odor Perfumed.

# **Precautionary Statements - Prevention**

Avoid breathing fumes, mist, vapors or spray. Use only outdoors or in a well-ventilated area

#### **Precautionary Statements - Response**

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor if you feel unwell.

#### **Precautionary Statements - Storage**

Protect from sunlight. Store in a well-ventilated place

## Hazards not otherwise classified (HNOC)

#### Other Information

Causes mild skin irritation
No information available

# 3. Composition/information on Ingredients

Common Name Glass Cleaner.
Synonyms Glass Cleaner.
Chemical Family MIXTURES.
Formula 7-7694-1

Chemical nature Aqueous solution of organic solvent.

Chemical name	CAS No	weight-%	Trade secret
Water	7732-18-5	85-90	*
2-Butoxyethanol	111-76-2	1-5	*
N-Butane	106-97-8	1-5	*
Propane	74-98-6	1-5	*

Chemical Additions

Hazardous components according to OSHA, are listed when present at 1% or greater. Carcinoges are listed when present at 0.1% or greater.

## 4. First aid measures

# **FIRST AID MEASURES**

Eye Contact Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact

lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control

center or doctor for treatment advice.

**Skin contact**Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

physician.

inhalation If overcome by vapor, move person to fresh air. Restore respiration if necessary. Get

medical attention if injury develops.

**INGESTION** Ingestion from an aerosol product is unlikely to occur.

## Most important symptoms and effects, both acute and delayed

**Symptoms** Acute, Deliberate inhalation of concentrated vapor or mist may cause headaches.

Prolonged and repeated contact with the eyes may cause mild irritation. Chronic:

2-butoxyethanol may cause hemolysis of the blood cells leading to possible liver and kidney

damage.

## Indication of any immediate medical attention and special treatment needed

Note to physicians None needed.

<sup>\*</sup> The exact percentage (concentration) of composition has been withheld as a trade secret.

# 5. Fire-fighting measures

### Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

#### Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may release carbon monoxide and carbon dioxide.

# **Explosion data**

Sensitivity to Mechanical Impact Contents under pressure, keep away from heat and open flame.

Sensitivity to Static Discharge Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

**Personal precautions**Use with adequate general or local exhaust ventilation.

For emergency responders Remove all sources of ignition.

**Environmental Precautions** 

**Environmental Precautions** See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Provide adequate ventilation to area being treated. Soak up spills with chemically inert,

absorbent material.

**Methods for cleaning up**Clean contaminated surface thoroughly.

# 7. Handling and Storage

Precautions for safe handling

Advice on safe handling Do not deliberately inhale vapor or spray mist. Avoid getting spray into eyes.

Conditions for safe storage, including any incompatibilities

**Storage Conditions** Store in a cool, dry place away from heat and open flame. Keep out of reach of children.

**AEROSOL STORAGE LEVEL I (NFPA-30B).** 

**Incompatible Materials** Avoid heat, open flame and contact with strong oxidizers.

# 8. Exposure Controls/Personal Protection

Control parameters

**Exposure guidelines** See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-Butoxyethanol	TWA: 20 ppm	TWA: 50 ppm	IDLH: 700 ppm

111-76-2		TWA: 240 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m³ (vacated) S* S*	TWA: 5 ppm TWA: 24 mg/m³
N-Butane 106-97-8	STEL: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m³
Morpholine 110-91-8	TWA: 20 ppm S*	TWA: 20 ppm TWA: 70 mg/m³ (vacated) TWA: 20 ppm (vacated) TWA: 70 mg/m³ (vacated) STEL: 30 ppm (vacated) STEL: 105 mg/m³ (vacated) S* S*	IDLH: 1400 ppm TWA: 20 ppm TWA: 70 mg/m³ STEL: 30 ppm STEL: 105 mg/m³

## **Appropriate engineering controls**

### Individual protection measures, such as personal protective equipment

**Eye/face Protection** Conventional eyeglasses to guard against splashing.

**Skin and Body Protection** Household type gloves, if desired.

**Respiratory protection** None required if used in a well-ventilated area .

**General hygiene considerations** Wash hands thoroughly after handling.

# 9. Physical and Chemical Properties

# Information on basic physical and chemical properties

Physical State Foam Aerosol

Appearance Clear liquid that will be aerosolized. Odor Perfumed.

Color Clear Odor threshold No information available

PropertyValuesRemarks • MethodpH10.95 - 11.01No information availableMelting point/freezing pointNot applicableNo information available

**Boiling point/boiling range** Water 212 °F/100 °C No information available **Flash Point** Not applicable. This is an aerosol No information available

product for which Flame Projection is 0 in. with 0 in flashback. Product was tested for Enclosed Space Ignition Test and is not a flammable aerosol as

defined on 29CFR 1910.122 Appendix

B.3.

**Evaporation Rate** Faster than butyl acetate No information available

Flammability (solid, gas)

No information available
Flammability Limits in Air

No information available

Upper flammability limits Not available

Lower Flammability Limit Not available

Vapor pressure No information available

Vapor DensityNo information availableSpecific gravity0.992 - 1.102 concentrateNo information availableWater solubilitySoluble in water

Water solubility
Soluble in water
No information available
Partition coefficient
No information available

Autoignition Temperature Decomposition temperature

No information available No information available No information available No information available

Kinematic viscosity Dynamic viscosity Explosive properties

**Oxidizing properties** 

No information available No information available

Other Information

Softening pointNo information availableMolecular weightNo information available

**VOC content (%)** 8.88%

**Density** 8.26 - 8.35 lb/gal **Bulk Density** No information available

# 10. Stability and Reactivity

#### Reactivity

Not applicable Not applicable

### **Chemical stability**

Stable.

### Possibility of hazardous reactions

Temperatures above 120 F may cause cans to burst with force.

hazardous polymerization Hazardous polymerization does not occur.

# **Conditions to Avoid**

Temperatures above 120 F.

#### **Incompatible Materials**

Avoid heat, open flame and contact with strong oxidizers.

# **Hazardous decomposition products**

Thermal decomposition may yield gases like carbon monoxide and carbon dioxide.

# 11. Toxicological Information

## Information on likely routes of exposure

Product Information Primary routes of entry: Eye contact, skin contact, inhalation, ingestion (possible, but

consider unlikely).

**inhalation** Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and

nausea.

**Eye Contact** Can cause irritation after contact with eyes.

**Skin contact** May cause skin irritation after contact with skin. 2-Butoxyethanol penetrates skin readily.

Frequent or wide spread contact may results on skin absorption of potentially harmful

amounts.

**INGESTION** This is an aerosol product, ingestion is unlikely to occur. 2-Butoxyethanol may cause red

blood cell hemolysis and possible liver and kidney damage.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Water 7732-18-5	> 90 mL/kg ( Rat )	-	-
2-Butoxyethanol 111-76-2	= 470 mg/kg ( Rat )	= 99 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h
N-Butane 106-97-8	-	-	= 658 g/m³ ( Rat ) 4 h
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h

#### Information on toxicological effects

Symptoms Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and

nausea.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation**May cause skin irritation after contact with skin. 2-Butoxyethanol penetrates skin readily.

Frequent or wide spread contact may results on skin absorption of potentially harmful

amounts.

Serious eye damage/eye irritation Can cause irritation after contact with the eyes.

corrosivityNot applicable.sensitizationNo a skin sensitizer.Germ Cell MutagenicityNo information available.

carcinogenicity Not known chronic effects based on available data. None of the ingredients present in

excess of 0.1% are listed as carcinogenic by NTP, IARC or OSHA.

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Aspiration Hazard Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and

nausea.

#### Numerical measures of toxicity - Product Information

# The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 9812 mg/kg
ATEmix (dermal) 22965 mg/kg
ATEmix (inhalation-gas) 14583 mg/l
ATEmix (inhalation-dust/mist) 31.3 mg/l
ATEmix (inhalation-vapor) 5821 mg/l

# 12. Ecological Information

This product does not contain marine pollutants.

#### ecotoxicity

4.96% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
2-Butoxyethanol		1490: 96 h Lepomis		1000: 48 h Daphnia magna
111-76-2		macrochirus mg/L LC50		mg/L EC50 1698 - 1940: 24
		static 2950: 96 h Lepomis		h Daphnia magna mg/L
		macrochirus mg/L LC50		EC50

#### Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

Chemical name	Partition coefficient
2-Butoxyethanol 111-76-2	0.81
N-Butane 106-97-8	2.89
Propane 74-98-6	2.3

Other adverse effects No information available

# 13. Disposal Considerations

Waste treatment methods

**Disposal of wastes**Dispose of in accordance with federal, state and local regulations.

**Contaminated packaging** Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate

container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your

local solid waste agency for disposal instructions.

# 14. Transport Information

**DOT** Limited quantity (LQ) Glass Cleaner

UN/ID no UN1950

Proper Shipping Name Limited quantity (LQ)

Hazard Class 2.1

Marine pollutant This product does not contain marine pollutants.

# 15. Regulatory information

**International Inventories** 

TSCA All ingredients of this product are listed or are excluded from listing under the U.S. Toxic

Subtances Control Act (TSCA) Chemical Substance Inventory.

DSL All ingredients are listed or are excluded from listing on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

# **US Federal Regulations**

### **SARA 313**

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
2-Butoxyethanol - 111-76-2	111-76-2	1-5	1.0

# SARA 311/312 Hazard Categories

Acute Health Hazard	yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

# **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

## **US State Regulations**

## **California Proposition 65**

This product does not contain any Proposition 65 chemicals

# U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Water 7732-18-5			Х
2-Butoxyethanol 111-76-2	Х	X	Х
N-Butane 106-97-8	Х	X	Х
Propane 74-98-6	Х	Х	Х

## U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information				
<u>NFPA</u>	Health Hazards 1	Flammability 1	Instability 1	Physical and chemical properties Not applicable
<u>HMIS</u>	Health Hazards 1	Flammability 2	Physical Hazards 1	Personal Protection B - Eyes and hands protection

Issue date 23-Feb-2015

**Revision note** 

This SDS supersedes a previous SDS dated September 24, 2014.

#### <u>Disclaimer</u>

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**